


# Cylindrical and Spherical Inflatable Stoppers



HFT PIPESTOPPERS®

## Expansion ranges

Inflatable Stopper size Nominal diameter	Min ID MM	Max ID MM	Inflatable Stopper size Nominal diameter	Min ID MM	Max ID MM
1" - 25 mm	24	28	23" - 575 mm	570	580
2" - 50 mm	45	55	24" - 600 mm	595	605
3" - 75 mm	70	80	26" - 650 mm	645	655
4" - 100 mm	95	105	27" - 675 mm	670	680
5" - 125 mm	120	130	28" - 700 mm	695	705
6" - 150 mm	145	155	30" - 750 mm	745	755
7" - 175 mm	170	180	32" - 800 mm	795	805
8" - 200 mm	195	205	34" - 850 mm	845	855
9" - 225 mm	220	230	36" - 900 mm	895	905
10" - 250 mm	245	255	39" - 1000 mm	995	1005
11" - 270 mm	270	280	44" - 1100 mm	1095	1105
12" - 300 mm	295	305	48" - 1200 mm	1195	1205
13" - 325 mm	320	330	51" - 1300 mm	1295	1305
14" - 350 mm	345	355	55" - 1400 mm	1395	1405
15" - 375 mm	370	380	60" - 1500 mm	1495	1505
16" - 400 mm	395	405	63" - 1600 mm	1595	1605
17" - 425 mm	420	430	67" - 1700 mm	1695	1705
18" - 450 mm	445	455	71" - 1800 mm	1795	1805
19" - 475 mm	470	480	75" - 1900 mm	1895	1905
20" - 500 mm	495	505	80" - 2000 mm	1995	2005
21" - 525 mm	520	530	96" - 2440 mm	2100	2500
22" - 550 mm	545	555			

### Additional Technical Information

1" to 24" (25 to 600 mm) **Inflatable Stoppers** have a 1.3 m hose length, 8 mm ID, 14 mm OD and are fitted with a Schrader valve for inflation and deflation.

25 to 96" (650 to 2440 mm) **Inflatable Stoppers** have a 2 m hose length, 10 mm ID, 12 mm OD and are fitted with a metal ball valve with a BSP connection.